



Befindo

Befindo Sejahtera Electronics

ALINCO DJ-C7 Dual Band Handy Talkie

Handy Talkie Dual Band ALINCO DJ-C7 dengan spesifikasi : GENERAL Frequency Coverage: T/ USA model TX/ RX: 144-147.995MHz/ 420-449.995MHz RX: 88.1-107.995/ 108-173.995/ 380-511.995MHz AM/ FM/ WFM E/ EU model TX/ RX: 144-145.995MHz/ 430-439.995MHz RX: 87.5-107.995MHz WFM Modulation: TX: 16k0F3E (FM) RX: WFM/ FM/ AM (where permitted) Receiver System: Double Conversion Super-heterodyne (WFM: Single CSH) Channel Step: Auto/ 5/ 6.25/ 8.33/ 10/ 12.5/ 15/ 20/ 25/ 30/ 50/ 100/ 125/ 200KHz Memory Channels: 200ch with 5 PS pairs, 1 priority and 1 auto-repeater pair Tone Encoder: 39 tone encoder standard Tone Decoder: 39 tone decoder standard Offset range: 0 ~ 99.995MHz Deviation: + / - 5KHz TX Output: 300mW with EBP58N / 500mW with 6Vdc power-source TX Spurious emissions: less than -60dB Frequency Stability: -7 to + 3ppm (-10 ~ + 50 degrees C.) Sensitivity (12dBSINAD) : Ham-bands VHF: -14dBu UHF: -12dBu / WFM -3dBu average Selectivity: + / -12KHz or more(-6dB) + / -35KHz or less (-60dB) I.F.: 1st: 50.85MHz(WFM 10.7MHz) 2nd: 450KHz AF output: 100mW or more (MAX) , 90mW or more (10% dist. 8 ohm) at 6.0Vdc Power Supply Requirements: 3.7Vdc EBP58N / 3.7 - 6.0Vdc external power source Current Drain (approx) : TX: 320mA / RX (squelched) : 70mA / RX (BS-on) : 19mA Operating Temperature: -10 ~ + 60 degrees C, 14 ~ 140 degrees F Dimensions: 56(W) x 96(H) x 14.5(D) mm (without projections) or 2.28 x 3.78 x 0.57 inches Weight: approx. 102g or 3.59oz antenna/ EBP58N inclusive

[Vendor Information](#)

Customer Reviews: There are yet no reviews for this product.
Please log in to write a review.